



**ORDER MATRIX** | Example: K3023L

<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>E</u>	<u>F</u>
<b>A</b>	Series				
<b>K3023L</b>	COB Track Lighting (50W)				
<b>B</b>	Finish				
<b>WH</b>	White				
<b>BK</b>	Black				
<b>SV</b>	Silver				
<b>SN</b>	Satin Nickel				
<b>C</b>	Power Supply				
<b>ND120</b>	Non-Dimming 120V				
<b>ND277</b>	Non-Dimming 277V				
<b>D120</b>	0-10V Dimming 120V				
<b>D277</b>	0-10V Dimming 277V				
<b>D</b>	LED Available				
<b>Philips</b>	Philips				
<b>Cree</b>	Cree				
<b>Epistar</b>	Epistar				
<b>Seoul</b>	Seoul				
<b>Osram</b>	Osram				
<b>E</b>	Color Temperature				
<b>27K</b>	2700K				
<b>30K</b>	3000K				
<b>40K</b>	4000K				
<b>50K</b>	5000K				
<b>60K</b>	6000K				
<b>F</b>	Beam Spread				
<b>16°</b>	16° Spot				
<b>24°</b>	24° Narrow Flood				
<b>32°</b>	32° Flood				
<b>50°</b>	50° Wide Flood				

**LED Light Engine:**

- Color Temperature 2700K-6000K
- CRI 80+
- 3 Step MacAdam (3 SDMC)
- Passive aluminum heat sink
- 50,000 hrs average rated life

**Electrical System:**

- 120V/277V 50/60Hz input
- Over voltage, over current and short circuit protection: Auto recovery
- MTBF > 100,000 hours

**Optics:**

- 16° Spot, 24° Narrow Flood, 32° Flood, and 50° Wide Flood

**Dimming:**

- Track Dimming
  - (ELV) reverse phase control dimmers. 120V only.
  - Dimmable 100 – 10%
- Canopy Dimming
  - ELV Dimming 120V
  - 0-10V Dimming 120V or 277V

**Compatibility:**

- Track luminaire is designed for use with the following track systems:
  - Single Circuit/Single Neutral 120V
  - Two Circuit/Single Neutral 120V
  - Two Circuit / Two Neutral 120V
  - Two Circuit / Two Neutral 277V

**Listing & Warranty:**

- ETL Listed to US and Canadian standards for dry locations
- 5-Year Limited Warranty