

# UC1250

## T5 Under Cabinet Light

<b>Catalog #</b>		<b>Prepared by</b>	LiteHarbor
<b>Project</b>		<b>Date</b>	
<b>Notes</b>			



DG-UC1250	DG-UC2150	DG-UC3350	DG-UC4250
Length=12"	Length=21"	Length=33"	Length=42"
Width=5"	Width=5"	Width=5"	Width=5"
Height=1"	Height=1"	Height=1"	Height=1"
Watt=8	Watt=13	Watt=13+8	Watt=13+13



### T5 Under Cabinet Light

#### Features

- 1) Made of die-formed rolled steel
- 2) PC cover no UV no glare
- 3) Three primary colors good for eyes
- 4) Fixture is pre-wire for immediate hard wire connection to 120V power source
- 5) Integral class-P, 120V normal factor ballast for efficient operation
- 6) Powder coating is high temperature resistance

#### Lamp

1xT5 8/13/13+8/13+13W

Color temperature does at customers' requirements

#### Mounting

Two mountings crews provided for installation into wood surface two key hole slots located in the back of the fixture housing

#### Listing

cULus suitable for damp location



#### Order Matrix

	<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>
--	----------	----------	----------	----------

<b>Item No.</b> UC1250
------------------------

A	Series
U1250	T5 Fluorescent Under Cabinet Light/12"
U2150	T5 Fluorescent Under Cabinet Light/21"
U3350	T5 Fluorescent Under Cabinet Light/33"
U4250	T5 Fluorescent Under Cabinet Light/42"

B	Finish
WH	White
SV	Silver
BK	Black

C	Input
	120V
277	277V

D	Color Temperature
27K	2700K
30K	3000K
35K	3500K
41K	4100K
60K	6000K



CABINET LIGHT



**Liteharbor Lighting Technology Co., Ltd.**

New Industry Area Hecun Danzao Town  
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jan. 2015